

镜头参数 (Parameter of Lens)

型号 (Model) :

RSLN-S1F17-05Z-1250MMC-16M-N



| | | | | | | | |
|--------------------------------------|-------------------------|------------|---------------|-------------|------|----------|------|
| 分辨率 (Pixel) | 5 MegaPixel | | | | | | |
| 像面尺寸 (Image format) | 1/1.7" | | | | | | |
| 焦距 (Focal length) | 12~50 (±5%)mm | | | | | | |
| 通光孔径 (Aperture) | F1.6±10% | | | | | | |
| 接口 (Mount) | CS | | | | | | |
| 视场角 (Field Angle) D×H×V(°) ±5% | ° | 1/1.7(4:3) | | 1/1.8(16:9) | | 1/2(4:3) | |
| | | Wide | Tele | Wide | Tele | Wide | Tele |
| | D | 46.2 | 10.9 | 43.5 | 10.4 | 38.9 | 9.4 |
| | H | 36.3 | 8.8 | 37.5 | 9 | 30.7 | 7.5 |
| V | 26.8 | 6.6 | 20.6 | 5.1 | 22.8 | 5.6 | |
| 畸变 (Optical Distortion) | -10.4% | | | | | | |
| 最近物距 (M. O. D.) | 1.5m | | | | | | |
| 主光线角 (Chief Ray Angle) | 0.16° (Wide); 0° (Tele) | | | | | | |
| 重量 (Weight) | 260±5g | | | | | | |
| 外形尺寸 (Dimension) | φ47×87.2mm | | | | | | |
| 镀膜波段 (Coating Range) | 400-900nm | | | | | | |
| 法兰后焦距 (Flange BFL) | 12.5mm(in air) | | | | | | |
| 光学后焦距 (BFL) | >8.26mm(in air) | | | | | | |
| 机械后焦距 (MBF) | >6.95mm(in air) | | | | | | |
| 日夜共焦 (IR Correction) | Yes | | | | | | |
| 操作方法 (Operation) | 光圈 (Iris) | | 手动光圈 (Manual) | | | | |
| | 聚焦 (Focus) | | 手动聚焦 (Manual) | | | | |
| | 变焦 (Zoom) | | 手动变焦 (Manual) | | | | |
| 工作温度 (Operating temperature) | -30°C~+70°C | | | | | | |

尺寸 (Size)

